

3 PROVEN STEPS FOR ENDLESS HOT WATER

- 1** Find your location on the map and note the color block.



Represents a hand sink faucet opened full with a flow of 0.5 GPM (gallons per minute)



Represents a sink faucet opened half way with 1/2 the GPM



Represents a water-saver shower open full with 1.5 GPM



Represents a water-saver shower opened half way with 1/2 the GPM

- 2** Find the unit with your desired capacity that corresponds to your location color.

INLET TEMPERATURE: 37°F

MODEL	GPM	APPROX. USAGE
HA008240	0.80	
HA011240	1.10	
HA013240	1.31	
HA018240	1.81	
HA024240	2.41	
HA027240	2.71	
HA036240	3.62	

INLET TEMPERATURE: 42°F

MODEL	GPM	APPROX. USAGE
HA008240	0.87	
HA011240	1.19	
HA013240	1.41	
HA018240	1.95	
HA024240	2.60	
HA027240	2.93	
HA036240	3.90	

INLET TEMPERATURE: 47°F

MODEL	GPM	APPROX. USAGE
HA008240	0.94	
HA011240	1.30	
HA013240	1.53	
HA018240	2.12	
HA024240	2.83	
HA027240	3.18	
HA036240	4.24	

INLET TEMPERATURE: 52°F

MODEL	GPM	APPROX. USAGE
HA008240	1.03	
HA011240	1.42	
HA013240	1.68	
HA018240	2.32	
HA024240	3.09	
HA027240	3.48	
HA036240	4.64	

INLET TEMPERATURE: 57°F

MODEL	GPM	APPROX. USAGE
HA008240	1.14	
HA011240	1.57	
HA013240	1.85	
HA018240	2.56	
HA024240	3.42	
HA027240	3.84	
HA036240	5.12	

INLET TEMPERATURE: 62°F

MODEL	GPM	APPROX. USAGE
HA008240	1.27	
HA011240	1.75	
HA013240	2.06	
HA018240	2.86	
HA024240	3.81	
HA027240	4.29	
HA036240	5.72	

INLET TEMPERATURE: 67°F

MODEL	GPM	APPROX. USAGE
HA008240	1.44	
HA011240	1.98	
HA013240	2.34	
HA018240	3.24	
HA024240	4.31	
HA027240	4.85	
HA036240	6.47	

INLET TEMPERATURE: 72°F

MODEL	GPM	APPROX. USAGE
HA008240	1.66	
HA011240	2.28	
HA013240	2.69	
HA018240	3.73	
HA024240	4.97	
HA027240	5.59	
HA036240	7.45	

INLET TEMPERATURE: 77°F

MODEL	GPM	APPROX. USAGE
HA008240	1.95	
HA011240	2.68	
HA013240	3.17	
HA018240	4.39	
HA024240	5.85	
HA027240	6.59	
HA036240	8.78	

Results based on outlet temperature of 105°F and simultaneous operation of indicated fixtures.
For Puerto Rico and Hawaii, use ground water temperature of 72°F. For Alaska, use ground water temperature of 37°F.

- 3** Check dimensions and specifications in the chart below.

MODEL	KW	VOLTS	AMPS	WIRE GAUGE REQ.	BREAKER	CONNECTION
HA008240	8	240	33	1 x 8 AWG	1 x 40 AMPS	1/2" CF*
HA011240	11	240	46	1 x 6 AWG	1 x 50 AMPS	1/2" CF*
HA013240	13	240	54	1 x 6 AWG	1 x 60 AMPS	1/2" CF*
HA018240	18	240	75	2 x 8 AWG	2 x 40 AMPS	3/4" NPT
HA024240	24	240	100	3 x 8 AWG	3 x 40 AMPS	3/4" NPT
HA027240	27	240	112.5	3 x 8 AWG	3 x 40 AMPS	3/4" NPT
HA036240	36	240	150	4 x 8 AWG	4 x 40 AMPS	3/4" NPT

*NPT adapter provided.



VISIT
www.eemaxHA.com