60 x 32 x 74 inches



### **FEATURES**

- Tub-shower
- Smooth wall finish
- Ergonomic backrest
- Molded toiletry shelves
- Above-floor rough
- Slip-resistant textured bottom
- Left or right hand drain
- AcrylX<sup>™</sup> applied acrylic surface
- Lifetime limited warranty

## **OPTIONS**

- Grab bar reinforcement
- Factory installed assisted care grab bars
- Designer drain, waste & overflow
- Shower Door Series LO516

## AQUATIC ADVANTAGE

- National distribution
- 6 manufacturing facilities
- Private fleet
- Centralized customer service
- Field support

### **COLOR OPTIONS**

Stock	Upgraded	Premium
White	Almond Linen/Biscuit Bone	Black Mexican Sand Sand Bar Sterling Silver









# 2603SGM


 $60 \times 32 \times 74$  inches



AFR: Allows for above the floor installation of waste, overflow and drainage.







60"-

FEATURES Ibs

Dimensional Tolerance ± %". Dimensions needed for site preparation should be measured from the unit. Aquatic assumes no responsibility for preparatory work.


Model #	Material	Wall Finish	Jets	Motor	Controls	Drain	Net Wt.	Pkg. Wt.
AFR Tub-Shower #2603SGM	$AcrylX^{TM}$	Smooth	-	-	-	LH or RH	134	139

### **DIMENSIONS**

Specifications	inches
Width: Overall / Net	60
Depth: Overall / Net	33 ¼ / 32
Height: Overall / Net	75 1/4 / 74
Enclosure Opening	56
Skirt Height	17 1/4
Drain Rough-In (from Back Wall)	15
Drain Rough-In (from Side Wall)	2 3/4
Drain: Diameter / Clearance	2 / 3 1/4

### FRAMING DIMENSIONS inches

Туре	<b>D</b> Depth	<b>W</b> Width	<b>H</b> Height	А	В	С	
Alcove	33 1/4	60 1/8	_	Box Out	2 3/4	15	



### SUMP DATA

Top of Drain to Bottom of Overflow	Capacity	Min. Operating	WIDTH @ centerline		DEPTH @ centerline	
	to Overflow gal	Capacity — gal	Тор	Bottom	Тор	Bottom
<b>⊘ 7</b> ⁄8	42	-	53 <b>½</b>	45 <b>¾</b>	22 1/4	20 3⁄4