SAFETY DATA SHEET



Suma D9.6 Oven & Grill Cleaner

Version Number: 3

Preparation date: 2016-01-14

1. IDENTIFICATION

Product name: Product Code: SDS #: Recommended use:

Uses advised against:

Manufacturer, importer, supplier: US Headquarters Sealed Air 8215 Forest Point Blvd. Charlotte, NC 28273-5509 Phone: 1-888-352-2249 SDS Internet Address: https://sds.sealedair.com

Emergency telephone number:

Suma D9.6 Oven & Grill Cleaner 948049, 957278280 MS0800511 • Industrial/Institutional • Oven and Grill Cleaner Uses other than those identified are not recommended

> Canadian Headquarters Sealed Air - Canada 3755 Laird Road Mississauga, Ontario L5L 0B3 Phone: 1-800-668-7171

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation	Category 1A
Serious eye damage/eye irritation	Category 1
Metal Corrosion:	Category 1
	0,1



Signal Word:

Danger.

Precautionary Statements

CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY BE CORROSIVE TO METALS.

Avoid contact with eyes, skin and clothing. Causes burns/ serious damage to mouth, throat and stomach. Keep container tightly closed. Keep only in original container. Do not breathe spray. Wash affected areas thoroughly after handling. Wear chemical–splash goggles, long chemical-resistant gloves and protective footwear when spraying and wiping. Do not spray towards face. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Absorb spillage to prevent material damage. Store in corrosive-resistant container with a resistant inner liner. Dispose of unused content as chemical waste. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION:. Mix only with water. DO NOT MIX WITH ANY OTHER PRODUCT OR CHEMICAL. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat.

Suma D9.6 Oven & Grill Cleaner



Classification for the diluted product @ RTU

This product is intended to be used neat.

Precautionary Statements

SUPPLEMENTAL INFORMATION:. Mix only with water. DO NOT MIX WITH ANY OTHER PRODUCT OR CHEMICAL. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS #	Weight %
Sodium hydroxide	1310-73-2	5 - 10%
Diethylene glycol butyl ether	112-34-5	1% - < 3%

*Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

<u>Most Important Symptoms/Effects:</u> No information available. <u>Immediate medical attention and special treatment needed</u> Not applicable.

Diluted Product:

Eyes: Rinse with plenty of water If irritation occurs and persists, get medical attention. **Skin:** Rinse with plenty of water If irritation occurs and persists, get medical attention. **Inhalation:** No specific first aid measures are required **Ingestion:** Rinse mouth with water.

5. FIRE-FIGHTING MEASURES

Specific methods: Suitable extinguishing media: Specific hazards: No special methods required Not applicable. Not applicable.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Environmental precautions and clean-up methods: No information available. Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: ALWAYS WEAR LONG CHEMICAL-RESISTANT GLOVES, CHEMICAL-SPLASH GOGGLES AND PROTECTIVE FOOTWEAR WHEN SPRAYING AND WIPING. Do not spray toward face. Wash hands and arms after use. Do not spray on or let spray contact pilot light,

electrical connections, switches, light bulbs, heating elements, receptacles, or thermostats. Spray may cause electric short. Do not let product contact floor coverings, linoleum, aluminum, copper, chrome, painted surfaces or plastics. Do not use on continuous or self-cleaning ovens. Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Mix only with water. Do not mix with any other product or chemical. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Aerosol Level (if applicable) : Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

None known Personal Protective Equipment Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A rest that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be workplace conditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.	2 mg/m³ (TWA) -				
Undiluted Product: Engineering measures to reduce exposure: None known Personal Protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective Respiratory protection: Protective footwear. If major exposure is possible, wear suitable protective In case of insufficient ventilation wear suitable respiratory equipment. A rest that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must hove workplace conditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respiratories in an anintained.	-				
Engineering measures to reduce exposure: None known Personal Protective Equipment Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A rest that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be workplace conditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
Engineering measures to reduce exposure: None known Personal Protective Equipment Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A rest that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be workplace conditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
None known Personal Protective Equipment Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A rest that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be workplace conditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
Personal Protective Equipment Chemical-splash goggles. Eye protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective Respiratory protection: Protective footwear. If major exposure is possible, wear suitable protective In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory enditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective. Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A rest that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be workplace conditions warrant a respirator's use. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respiratory exposure					
Hand protection: Chemical-resistant gloves. Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection: Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective. Respiratory protection: Protective footwear. If major exposure is possible, wear suitable protective. Hygiene measures: Protective footwear. If major exposure is possible, wear suitable protective. Diluted Product: Handle in accordance with good industrial hygiene and safety practice. This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection: Hygiene measures: In case of insufficient ventilation wear suitable respiratory equipments must be workplace conditions warrant a respirator's use. Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.					
Hygiene measures: that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must I workplace conditions warrant a respirator's use. Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.	Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.				
Hygiene measures: workplace conditions warrant a respirator's use. Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respired if good ventilation is maintained.	In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program				
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respreduired if good ventilation is maintained.	be followed whenever				
Diluted Product: This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respondered if good ventilation is maintained.					
This product is intended to be used neat. Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Respondered if good ventilation is maintained.	Handle in accordance with good industrial hygiene and safety practice.				
Engineering measures to reduce exposure: Good general ventilation should be sufficient to control airborne levels Resp required if good ventilation is maintained.					
required if good ventilation is maintained.					
	ure: Good general ventilation should be sufficient to control airborne levels Respiratory protection is not				
Personal Protoctive Equipment	required if good ventilation is maintained.				
Personal Protective Foundment					
Eye protection: Chemical-splash goggles.					
Hand protection: Long chemical-resistant gloves.					
Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective	clothing and footwear.				
Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A res	· · · · · · · · · · · · · · · · · · ·				
that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must I	spiratory protection progra				
workplace conditions warrant a respirator's use.					
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.					

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid	Color: Clear Tan
Evaporation Rate: No information available	Odor: Glycol Ether
Odor threshold: No information available.	Boiling point/range: Not determined
Melting point/range: Not determined	Decomposition temperature: Not determined
Autoignition temperature: No information available	Solubility: Completely Soluble
Solubility in other solvents: No information available	Relative Density (relative to water): 1.074
Density: 8.96 lbs/gal 1.074 Kg/L	Vapor density: No information available
Bulk density: No information available	Vapor pressure: No information available.
Flash point: > 200 °F > 93.3 °C	Partition coefficient (n-octanol/water): No information available
Dilution Flash Point: > 200 °F > 93.3 °C	Viscosity: No information available
Elemental Phosphorus: 0.00 % by wt.	VOC: 0 % *
pH: 12.57	VOC % by wt. at use dilution 0 % *
Dilution pH: 12.57 @ RTU	Flammability (Solid or Gas): Not applicable
Metal Corrosion: Category 1	
Explosion limits: - unner: Not determined - lower: Not determined	

Explosion limits: - upper: Not determined - lower: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity:

Not Applicable

Stability: Possibility of hazardous reactions: Hazardous decomposition products: Materials to avoid: Conditions to avoid: The product is stable May vigorously react with acids resulting in spattering and excessive heat. None reasonably foreseeable. Strong acids. Do not mix with any other product or chemical unless specified in the use directions. No information available.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Ingestion, Eye contact

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed). **Eye contact:** Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea. **Inhalation:** May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

Sensitization: No known effects.

Target Organs (SE): None known

Target Organs (RE): None known

Numerical measures of toxicityATE - Oral (mg/kg):>5000

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

 Waste from residues / unused products:
 This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)).

 Contaminated Packaging:
 Do not re-use empty containers.

 RCRA Hazard Class (undiluted product):
 D002 Corrosive Waste

 RCRA Hazard Class (diluted product):
 Not Applicable

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, **only available through Internet Explorer**, http://naextranet.diversey.com/dot/, for up to date shipping information.

DOT (Ground) Bill of Lading Description: UN1824, SODIUM HYDROXIDE SOLUTION, 8, II

IMDG (Ocean) Bill of Lading Description: UN1824, SODIUM HYDROXIDE SOLUTION, 8, II

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Sodium hydroxide	1310-73-2	Х	Х	Х	Х
Diethylene glycol butyl ether	112-34-5	-	Х	-	-
Sodium gluconate	527-07-1	-	-	-	-
Alkyl Glucoside	68515-73-1	-	-	-	-

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Sodium hydroxide	1310-73-2	5 - 10%	1000		
Diethylene glycol butyl ether	112-34-5	1% - < 3%			X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether	Х		

SARA 311/312 Hazard Categories

Immediate:	Х
Delayed:	-
Fire:	-
Reactivity:	-
Sudden Release of Pressure:	-

Canadian Regulations

16. OTHER INFORMATION

NFPA (National Fire Protection Association) Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3 Flammability 0 Instability 0

Version Number: 3 Preparation date: 2016-01-14

 Reason for revision:
 Not applicable

 Prepared by:
 NAPRAC

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.