

# MATERIAL SAFETY DATA SHEET

# 1. Product and Company Identification

Identification of the

preparation

HP LaserJet 92298A-X Print Cartridge

**Product use** This product is a toner preparation that is used in HP LaserJet 4/4 Plus/4M/4M Plus/5/5M series

printers.

Version # 06

07-Dec-2012 **Revision date** 

Hewlett-Packard Company Company identification

3000 Hanover Street Palo Alto, CA 94304-1185

**United States** 

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 **HP Customer Care Line** 

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

# 2. Hazards Identification

Acute health effects

Skin contact Unlikely to cause skin irritation. **Eve contact** May cause transient slight irritation

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

**Potential health effects** 

**Routes of exposure** Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK, NTP,

OSHA or ACGIH.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, as amended.

This preparation contains no component classified as Persistent, Bioaccumulative, and Toxic (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC)

1907/2006.

# 3. Composition / Information on Ingredients

Components	CAS #	Percent
Iron oxide	1317-61-9	< 55
Styrene acrylate copolymer	Trade Secret	< 55
Amorphous silica	7631-86-9	< 3

## 4. First Aid Measures

#### First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Material name: 92298A-X MSDS US

**Skin contact** Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

**Inhalation** Move person to fresh air immediately. If irritation persists, consult a physician.

**Ingestion** Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

**General advice** No additional information

# 5. Fire Fighting Measures

Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixtures when finely

dispersed in air.

**Extinguishing media** 

Suitable extinguishing

media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

**Protection of firefighters** 

Protective equipment and precautions for firefighters

If fire occurs in the printer, treat as an electrical fire.

**Specific methods** None established.

Hazardous combustion products

Carbon monoxide and carbon dioxide.

#### 6. Accidental Release Measures

**Personal precautions** Minimize dust generation and accumulation.

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

**Other information** Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a

damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust

explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with

federal, state, and local regulations.

7. Handling and Storage

**Handling** Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Keep

away from excessive heat, sparks, and open flames. Use with adequate ventilation.

**Storage** Keep out of the reach of children. Keep tightly closed and dry. Store away from strong oxidizers.

Store at room temperature.

## 8. Exposure Controls / Personal Protection

**Exposure guidelines** USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

**Engineering controls** Use in a well ventilated area.

Personal protective equipment

**General** No personal respiratory protective equipment required under normal conditions of use.

## 9. Physical & Chemical Properties

**Appearance** Fine powder **Color** Black.

Odor Slight plastic odor
Odor threshold Not available.

Physical state Solid Form solid

pH Not applicableMelting point Not available.Freezing point Not available.

Material name: 92298A-X

**Boiling point** Not applicable Flash point Not applicable **Evaporation rate** Not available. Flammability limits in air, Not available. upper, % by volume

Flammability limits in air, lower, % by volume

Not flammable

Vapor pressure Not applicable Vapor density Not available.

1.4 - 1.6 (H2O = 1)Specific gravity

Relative density Not available.

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

**Auto-ignition temperature** Not applicable **Decomposition temperature** > 392 °F (> 200 °C)

Softening point 212 - 302 °F (100 - 150 °C)

**Viscosity** Not applicable Percent volatile 0 % estimated VOC Not available.

# 10. Chemical Stability & Reactivity Information

Chemical stability Stable under normal storage conditions. Imaging Drum: Exposure to light Conditions to avoid

Incompatible materials Strong oxidizers

**Hazardous decomposition** 

products

Carbon monoxide and carbon dioxide.

Directive 67/548/EEC and as amended.

**Possibility of hazardous** Will not occur.

reactions

## 11. Toxicological Information

Carcinogenicity Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA

Regulations (USA), EU Directive, or Proposition 65 (California).

# IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Serious eye damage/eye

Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

irritation

No information available.

**Chronic toxicity** 

Sensitization Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA

HCS (US).

Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium) Mutagenicity

Reproductivity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65,

and DFG (Germany).

**Further information** Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

# 12. Ecological Information

**Ecotoxicity** LL50: > 1000 mg/l, Fish, 96.00 Hours

Persistence and degradability Not available.

Other adverse effects This product has not been tested for ecological effects.

Material name: 92298A-X MSDS US

# 13. Disposal Considerations

#### **Disposal instructions**

Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

# 14. Transport Information

#### **Further information**

13 or more of these cartridges shipped together in a single package (e.g., box, container), by air, are regulated as a magnetized material. These requirements do not apply to single or dual pack cartridges contained in an original HP package and shrink wrapped on a pallet for shipment by air.

#### **DOT**

Not regulated as dangerous goods.

#### **IATA**

### **Basic shipping requirements:**

Proper shipping name

Magentized Material

UN number 2807

#### **IMDG**

Not regulated as dangerous goods.

#### **RID**

Not regulated as dangerous goods.

# 15. Regulatory Information

**US federal regulations** 

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA.

#### **DEA Exempt Chemical Mixtures Code Number**

Not regulated.

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Not listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA (Superfund) reportable quantity**

None

#### Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200

No

hazardous chemical

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

No

ilazaruous substance

No

Section 311 hazardous chemical

#### State regulations

## **US. Massachusetts RTK - Substance List**

Amorphous silica (CAS 7631-86-9)

### **US. New Jersey Worker and Community Right-to-Know Act**

Not regulated.

Material name: 92298A-X MSDS US

### **US. Pennsylvania RTK - Hazardous Substances**

Amorphous silica (CAS 7631-86-9)

**US. Rhode Island RTK** 

Not regulated.

**Regulatory information** All chemical substances in this HP product have been notified or are exempt from notification

Listed.

under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

16. Other Information

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

**HMIS®** ratings Health: 1

> Flammability: 1 Physical hazard: 0

Health: 1 NFPA ratings

> Flammability: 1 Instability: 0

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

> Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as quaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and

may not meet regulatory requirements in other countries.

**Issue date** 07-Dec-2012

This data sheet contains changes from the previous version in section(s):

Composition / Information on Ingredients: Ingredients

9. Physical & Chemical Properties: Color

9. Physical & Chemical Properties: Other information

**Manufacturer information Hewlett-Packard Company** 

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

#### **Explanation of abbreviations**

American Conference of Governmental Industrial Hygienists **ACGIH** 

CAS Chemical Abstracts Service

**CERCLA** Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

**EPCRA** Emergency Planning and Community Right-to-Know Act (aka SARA)

**IARC** International Agency for Research on Cancer

**NIOSH** National Institute for Occupational Safety and Health

NTP **National Toxicology Program** 

**OSHA** Occupational Safety and Health Administration

PEL Permissible Exposure Limit

**RCRA** Resource Conservation and Recovery Act

REC Recommended

**REL** Recommended Exposure Limit

**SARA** Superfund Amendments and Reauthorization Act of 1986

**STEL** Short-Term Exposure Limit

**TCLP** Toxicity Characteristics Leaching Procedure

**TLV** Threshold Limit Value

**TSCA** Toxic Substances Control Act VOC Volatile Organic Compounds

Material name: 92298A-X MSDS US 5/5