

# MATERIAL SAFETY DATA SHEET

#### 1. Product and Company Identification

Material name	HP Color LaserJet Q6460A Black Print Cartridge
Use of the preparation	This product is a black toner preparation that is used in HP Color LaserJet 4730mfp/CM4730mfp series printers.
Version #	06
Revision date	03-08-2009
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-1501
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomerinquiries@hp.com
Date prepared	Mar 07, 2009
MSDS number	353350
lazards Identification	
Acute health effects	
Skin contact	Unlikely to cause skin irritation.
Eye contact	May cause transient slight irritation
Inhalation	Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust.
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.
Potential health effects	
Routes of exposure	Potential routes of exposure under normal use conditions are skin, eye contact and inhalation
	Ingestion is not expected to be a primary route of exposure for this product under normal us conditions.
Chronic health effects	Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this product as intended does not result in inhalation of excessive amounts of dust.
Carcinogenicity	Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present this carcinogenic risk.
Other information	This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, as amended.
	This preparation contains no component classified as Persistent, Bioaccumulative, and Tox (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC 1907/2006.

### 3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	< 85	
Wax	Trade Secret	< 15	
Carbon black	1333-86-4	< 6	
Amorphous silica	7631-86-9	< 2	

#### 4. First Aid Measures

at least 15 minutes or until particles are removed. If iritation persists, consult a physical   Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if in develops or persists.   Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.   Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, co physician.   5. Fire Fighting Measures Flash point and method   Not applicable Carbon monoxide and carbon dioxide.   products Carbon monoxide and carbon dioxide.   Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media Suitable extinguishing media   Suitable extinguishing media Unsuitable extinguishing media   Unsuitable extinguishing media Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters Protective equipment and precautions for firefighters   Protective equipment and precautions If fire occurs in the printer, treat as an electrical fire.   Social firefighting procedures None established.   6. Accidental Release Measures Personal precautions   Personal precautions Minimize dust generation and accumulatio	FIRST AID Measures	
at least 15 minutes or until particles are removed. If irritation persists, consult a physician.   Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.   Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, corphysician.   5. Fire Fighting Measures Flash point and method   Hazardous combustion Carbon monoxide and carbon dioxide.   products Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media C02, water, or dry chemical   Suitable extinguishing media C02, water, or dry chemical   Unsuitable extinguishing media Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters Protection of firefighters   Protection of firefighters If fire occurs in the printer, treat as an electrical fire.   Porsonal precautions Mone established.   6. Accidental Release Measures Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a dam	First aid procedures	
develops or persists. Move person to fresh air immediately. If irritation persists, consult a physician.   S. Fire Fighting Measures Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, corphysician.   S. Fire Fighting Measures Carbon monoxide and carbon dioxide.   Flash point and method Not applicable   Hazardous combustion Carbon monoxide and carbon dioxide.   products Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media CO2, water, or dry chemical   Unsuitable extinguishing media None known.   Unsuitable extinguishing media None known.   Unsuitable extinguishing media None known.   Protection of firefighters Protection of firefighters   Protection of firefighters None established.   6. Accidental Release Measures Minimize dust generation and accumulation.   Environmental precautions Minimize dust generation and accumulation.   Other information Slowip vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   Other information Slowiy vac	Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Ingestion   Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, corphysician.     5. Fire Fighting Measures   Flash point and method   Not applicable     Flash point and method   Carbon monoxide and carbon dioxide.     products   Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.     Extinguishing media   CO2, water, or dry chemical     Unusual fire and explosion hazard   None known.     Protection of firefighters   None known.     Protective equipment and precautions for firefighters   If fire occurs in the printer, treat as an electrical fire.     Protective equipment and precautions   Minimize dust generation and accumulation.     Do fi information   Slowy vacuum or sweep the material into a bag or other sealed container. Clean rem with adamp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosive or with federal, state, and local regulations.     Other information   Slowy vacuum or sweep the material into a bag or other sealed container. Clean rem with adequate ventilation. Keep away from excessive heat, sparks, and open flames Keep out of the reach of children. Store at nom temperature. Store away from store with adequate ventilation. Keep away from excessive heat, sparks, and open flames Keep out of the reach of children. Store at room temperature. Store away from store oxidaters. Keep tightly closed and dry.     8. Exposure Controls / Personal Pro	Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
strice physician.   5. Fire Fighting Measures Flash point and method   Flash point and method Not applicable   Hazardous combustion Carbon monoxide and carbon dioxide.   products Flammable properties   Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media Suitable extinguishing media   Suitable extinguishing media CO2, water, or dry chemical   Unusual fire and explosion hazard None known.   Inazurat Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters Protective equipment and precautions for firefighters   None established. None established.   6. Accidental Release Measures Personal precautions   Personal precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean re explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of chidren. Avoid inhalation of dust and contact with skin and	Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.
Flash point and method Not applicable   Flash point and method Not applicable   Carbon monoxide and carbon dioxide. Carbon monoxide and carbon dioxide.   Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media CO2, water, or dry chemical   Unsuitable extinguishing media None known.   Unusual fire and explosion hazard None known.   Protection of firefighters Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters If fire occurs in the printer, treat as an electrical fire.   Protective equipment and precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations. Other information   Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling Magnet Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.   Storage Keep out of the reach of children. Store at ro	Ingestion	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician.
Hazardous combustion products Carbon monoxide and carbon dioxide.   Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media Suitable extinguishing media CO2, water, or dry chemical   Unsuitable extinguishing media None known.   Unsuitable extinguishing media None known.   Unsuitable extinguishing media None known.   Unsuitable extinguishing media If fire occurs in the printer, treat as an electrical fire.   Protection of firefighters Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire.   Personal precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rer with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (R	Fire Fighting Measures	
products Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Extinguishing media CO2, water, or dry chemical   Suitable extinguishing media None known.   Unsuitable extinguishing media None known.   Protection of firefighters Frotective equipment and precautions for firefighters   Special firefighting procedures None established.   6. Accidental Release Measures Personal precautions   Personal precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proc. Fine powder can form explosive heat, sark, and open flames.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from strom oxidzers. Keep out of the reach of children. Store at room temperature. Store away from strom oxidzer	Flash point and method	Not applicable
finely dispersed in air.   Extinguishing media   Suitable extinguishing media   Unsuitable extinguishing media   Unusual fire and explosion hazard   Protection of firefighters   Protective equipment and precautions for firefighters   Special firefighting procedures   None established.   6. Accidental Release Measures   Personal precautions   Environmental precautions   Other information   Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage   Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames, Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection   Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 m		Carbon monoxide and carbon dioxide.
Suitable extinguishing media CO2, water, or dry chemical   Unsuitable extinguishing media None known.   Unsual fire and explosion hazard Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters If fire occurs in the printer, treat as an electrical fire.   Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire.   Personal precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rer with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.   Storage USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulat Amorphous silica: USA OSHA (TWA/PEL): 20 mpcf 80 (mg/m3)%SIO2, ACGIH	Flammable properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
media Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air.   Protection of firefighters Protective equipment and precautions for firefighters   Special firefighting procedures None established.   6. Accidental Release Measures Personal precautions   Personal precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rent with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in cont with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SIO2, ACGIH	Suitable extinguishing	CO2, water, or dry chemical
hazard finely dispersed in air.   Protection of firefighters Protective equipment and precautions for firefighters   Special firefighting procedures If fire occurs in the printer, treat as an electrical fire.   Special firefighting procedures None established.   6. Accidental Release Measures Personal precautions   Personal precautions Minimize dust generation and accumulation.   Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rer with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.   Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH		None known.
Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire.   Special firefighting procedures None established.   6. Accidental Release Measures Personal precautions   Personal precautions Minimize dust generation and accumulation.   Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.   Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Particulate, Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH		Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
precautions for firefighters Special firefighting procedures   None established.     6. Accidental Release Measures Personal precautions Environmental precautions   Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations.     Other information   Slowly vacuum or sweep the material into a bag or other sealed container. Clean ren with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.     7. Handling and Storage Handling   Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.     8. Exposure Controls / Personal Protection   USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Protection of firefighters	
6. Accidental Release Measures   Personal precautions Minimize dust generation and accumulation.   Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean remwith a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH		If fire occurs in the printer, treat as an electrical fire.
Personal precautions Minimize dust generation and accumulation.   Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations.   Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations.   7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage   Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Special firefighting procedures	None established.
Environmental precautionsDo not flush into surface water or sanitary sewer system. See also section 13 Dispositions.Other informationSlowly vacuum or sweep the material into a bag or other sealed container. Clean remwith a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations.7. Handling and Storage Handling StorageKeep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.8. Exposure Controls / Personal Protection Exposure guidelinesUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Accidental Release Measures	
Environmental precautionsDo not flush into surface water or sanitary sewer system. See also section 13 Dispositions.Other informationSlowly vacuum or sweep the material into a bag or other sealed container. Clean remwith a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations.7. HandlingKeep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.8. Exposure Controls / Personal ProtectionUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Personal precautions	Minimize dust generation and accumulation.
with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations.   7. Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulat Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	-	Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.
Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.   Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate)	Other information	Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.
Storage with adequate ventilation. Keep away from excessive heat, sparks, and open flames.   Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Handling and Storage	
oxidizers. Keep tightly closed and dry.   8. Exposure Controls / Personal Protection   Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate)   Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Handling	Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Us with adequate ventilation. Keep away from excessive heat, sparks, and open flames.
Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)   ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)   Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Storage	Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.
ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particula Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Exposure Controls / Personal P	Protection
Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Exposure guidelines	USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)
		ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)
Personal protective equipment General No personal respiratory protective equipment required under normal conditions of us		No personal respiratory protective equipment required under normal conditions of use.



### MATERIAL SAFETY DATA SHEET

#### 9. Physical & Chemical Properties

		-
	Appearance	Fine powder
	Color	Black
	Odor	Slight plastic odor
	Odor threshold	Not available.
	Physical state	Not available.
	Form	solid
	рН	Not applicable
	Melting point	Not available.
	Freezing point	Not available.
	Boiling point	Not applicable
	Flash point	Not applicable
	Evaporation rate	Not applicable
	Flammability	Not available.
	Flammability limits in air, upper, % by volume	Not available.
	Flammability limits in air, lower, % by volume	Not flammable
	Vapor pressure	Not applicable
	Vapor density	Not applicable
	Specific gravity	1 - 1.2 (H2O = 1)
	Relative density	Not available.
	Solubility (water)	Negligible in water. Partially soluble in toluene and xylene.
	Partition coefficient (n-octanol/water)	Not available.
	Auto-ignition temperature	Not applicable
	Decomposition temperature	Not available.
	Softening point	212 - 302 °F (100 - 150 °C)
	Viscosity	Not applicable
10	Chomical Stability & Reactivity	v Information

### 10. Chemical Stability & Reactivity Information

Chemical stability	Stable under normal storage conditions.
Conditions to avoid	Imaging Drum: Exposure to light
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Will not occur.
11. Toxicological Information	
Oral toxicity	LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful Not classified for acute oral toxicity according to EU Directive 67/548/EEC and 1999/45/EC.
Inhalation toxicity	No information available.
	Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and 1999/45/EC.
Eye irritation	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.

	MATERIAL SAFETY DATA SHEET
invent	
Sensitization	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).
Chronic toxicity	No information available.
Carcinogenicity	Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.
Mutagenicity	Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)
Reproductive toxicity	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, and DFG (Germany).
12. Ecological Information	
Ecotoxicity	96.00 Hours, LL50 > 1000 mg/l, rainbow trout
Persistence and degradability	Not available.
13. Disposal Considerations	
Disposal instructions	Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.
	HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.
14. Transport Information	
Not available.	
General	Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.
15. Regulatory Information	
US federal regulations	US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.
CERCLA (Superfund) reportable	e quantity
Superfund Amendments and Re Hazard categories	eauthorization Act of 1986 (SARA) Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	No
International regulations	All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.
16. Other Information	
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0



# MATERIAL SAFETY DATA SHEET

NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Issue date	Mar 7 2009 9:42PM
Revision	6
Replaces sheet dated	Aug 31 2008 2:24PM
Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
MSDS sections updated	1. Product and Company Identification: Use of the preparation Hazards Identification: Other information
Explanation of abbreviations	
ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer

CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SAR/
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209