

# LED PANEL LIGHT CATALOG NUMBER: KT-PLED40-14-8XX-VDIM





### **DESCRIPTION**

1'x4' LED Panel Light, 40W Family, 120-277V Input, 0-10V Dimming







# **PRODUCT FEATURES**


- Low Profile Architectural Grade Design
- Fits Standard T-Grid Ceilings
- Suitable for Surface or Suspension Mount with optional Accessories
- High Quality Laser Etched PMMA Resin Light Guide Plate offers optimal light diffusion with no risk of yellowing over product lifetime
- Powered by Keystone 0-10V Dimming LED driver with built in Junction Box
- · Listed on DLC QPL


- 7 Year Warranty
- 60,000 Hour Rated Life
- Over 50% Energy Savings as Compared to Traditional Fluorescent Troffers
- LED Color binning within 4 SDCM ensures supreme color consistency between all panels
- Operating Temperature Range: -20C to 40C
- Suitable for Damp Locations

# PERFORMANCE SPECIFICATIONS

| Catalog Number        | Input Voltage | Wattage | Color<br>Temperature | Lumen<br>Output | CRI   | Power Factor | Efficacy | Lifetime    |
|-----------------------|---------------|---------|----------------------|-----------------|-------|--------------|----------|-------------|
| KT-PLED40-14-835-VDIM | 120-277V      | 40W     | 3500K                | 4050lm          | >82.0 | >0.9         | 101lm/W  | 60,000 Hour |
| KT-PLED40-14-840-VDIM | 120-277V      | 40W     | 4000K                | 4100lm          | >82.0 | >0.9         | 103lm/W  | 60,000 Hour |
| KT-PLED40-14-850-VDIM | 120-277V      | 40W     | 5000K                | 4150lm          | >82.0 | >0.9         | 104lm/W  | 60,000 Hour |

# PHOTOMETRIC SPECIFICATIONS






| Zonal L | Zonal Lumen Summary |             |  |  |  |  |
|---------|---------------------|-------------|--|--|--|--|
| Zone    | Lumens              | % Luminaire |  |  |  |  |
| 0-30    | 1,071.3             | 26.6%       |  |  |  |  |
| 0-40    | 1,765.0             | 43.9%       |  |  |  |  |
| 0-60    | 3,151.1             | 78.4%       |  |  |  |  |
| 60-90   | 869.1               | 21.6%       |  |  |  |  |
| 70-100  | 368.3               | 9.2%        |  |  |  |  |
| 90-120  | 0.0                 | 0%          |  |  |  |  |
| 0-90    | 4,020.2             | 100%        |  |  |  |  |
| 90-180  | 1.1                 | 0%          |  |  |  |  |
| 0-180   | 4,021.3             | 100%        |  |  |  |  |

Keystone Technologies • 1390 Welsh Road, North Wales, PA 19454 • Phone (800) 464-2680 • Fax (888) 966-0556 • www.keystonetech.com



# LED PANEL LIGHT CATALOG NUMBER: KT-PLED40-14-8XX-VDIM

### PHYSICAL SPECIFICATIONS



### **WEIGHT INFORMATION**

| 1 pcs    | 1 ctn     |  |  |
|----------|-----------|--|--|
| 7.94 lb. | 18.41 lb. |  |  |

# **ACCESSORIES**

| Catalog Number    | Description   |
|-------------------|---|
| KT-PLED-SM-14-KIT | Surface Mount Kit for (1) 1x4 LED Panel Light                     |
| KT-PLED-EM-BR-KIT | Bracket Kit for Mounting Emergency LED Backup to LED Panel Lights |
| KT-PLED-CABLE-KIT | Cable Hanging Kit for LED Panel Lights (Includes 3 Cable Sets)    |

Accessories Sold Separately.

# **CATALOG NUMBER BREAKDOWN**

