## Part # MC304S | MC304SB









## SHORT PRODUCT DESCRIPTION

10 Year Tamper Proof Permanent Power Sealed Battery Carbon Monoxide Smart Alarm

## LONG PRODUCT DESCRIPTION

Provides protection against the silent killer—carbon monoxide. 10 year sealed power. No batteries to change—ever!

## **PRODUCT FEATURES & BENEFITS**

- Tamper proof design provides a higher level of security to prevent battery removal
- Maintenance Free Battery Power—No batteries to replace for life of the alarm. Gives a decade of peace of mind
- Saves money—Never replace batteries for 10 years, saving up to \$38.00 over the life of the alarm
- Eliminates annoying low battery chirps
- 10 year sealed batteries provide continuous protection—even in the event of a power outage
- Microprocessor intelligence combined with electrochemical sensor virtually eliminates nuisance alarms
- Ideal for installation in EVERY room. Perfect for new or replacement installations
- Red LED indicates the status of power and CO
- Table top (free standing) or wall mounted. Mounting hardware included
- Quick activation battery pull tab makes this fast and easy to install
- Deactivation key switches alarm off and makes batteries safe for disposal (once alarm reaches the 10 year product end of service life)
- Tamper resistant feature prevents deactivated alarm from being reinstalled
- Choose this alarm if you are looking for an alarm with superior nuisance alarm resistance
- 10 year product end-of-service life warning sounds when it is time to replace alarm
- This alarm is suitable for installation in houses, apartments, dormitories, hotels/motels & manufactured hsg
- For early warning of carbon monoxide, install this smart alarm on every level of dwelling, including basements
- For maximum protection, install an alarm inside every bedroom, outside every sleeping area and on every level of the dwelling
- Exceeds industry standards, ETL listed to UL Standard UL 2034 and California State Fire Marshal approved
- ECO Friendly—Reduces environmental waste & eliminates disposal of up to twenty 9 volt batteries
- Loud 85dB Alarm
- Temperature Range 40°F to 100°F (0°C to 38°C). Humidity Range 10% to 95% relative humidity (RH)
- 10 year limited warranty on both battery and alarm



