Permanent Marker Refill Page 1 of 3

			U.S. Department o	f			
Material Safety Data Sheet			Labor				
May be used to comply with			Occupational Safety and	d			
OSHA's Hazard Communication Standard			Health Administration(Non-				
29 CFR 1910.1200. Standard r			Mandatory Form)				
			Form Approved OMB No. 1218-0072				
IDENTITY (As used on Label an	.4 1:		Note: Blank spaces are not permitted. If any item is not				
Permanent Markers Re	applicable, or no information is available, the space must be marked to indicate that.						
(SCF,SCB,SC6600)	must be marked to indicate that.						
Black, Blue, Red, Green							
Section 1							
Manufacturer's Name	Telephone Number						
Pilot Corporation			03-3538-3700				
Address(Number, Street, City S			Fax Number				
2-6-21, Kyobashi 2-Chon	ie, Chuo-ku		03-3538-3909				
Touko 104 0204 Imar-			Date Prepared	,			
Toyko, 104-8304 Japan			September 25, 2007 Signature of Preparer(O				
7 TT TT T	**		1	puonar)			
Section II - Hazardous I	Ü			OSHA I	ori I.	CGIH Other Limits	0.1
Hazardous Component	s(Specific Chem	ical Identity;Co	ommon Name(s))	OSHA	ZEL A	ΓLV Recommended	% (option
NAME	CAS. NO.	TLV(PPM)	WT. (%)			COMPONENT	
Xylene	1330-20-7	100	56.3 - 67.6		Ink		
1-Butanol	71-36-3	100	7.5 - 18.0		Ink		
1-Methoxy-2-propanol	107-98-2	100	4.6 - 5.0	4.6 - 5.0		Ink (Black)	
					Barrel		
Aluminum	7429-90-5					Barrel	
Aluminum	7429-90-5					Barrel	
		acteristics				Barrel	
Aluminum Section III - Physical/Ch		acteristics				Specific	
Section III - Physical/Ch		acteristics	N.	<i>D</i> .		Specific Gravity	N.D
Section III - Physical/Ch		acteristics				Specific Gravity (H20=1)	
Section III - Physical/Ch		acteristics	N. N.			Specific Gravity (H20=1) Melting Point	
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg)		acteristics	N.	D.		Specific Gravity (H20=1)	N.D
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg)		acteristics	N.			Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate	N.D
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1)		acteristics	N.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate	N.L
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1)		acteristics	N.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate	N.D
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water N.D. Appearance and Odor		acteristics	N.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate	N.L
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water N.D. Appearance and Odor V.A.	nemical Char		N.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate	N.L
Section III - Physical/Ch Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water N.D. Appearance and Odor V.A. Section IV - Fire and Ex	emical Char	rd Data	N.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)	N.L
Section III - Physical/Che Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water N.D. Appearance and Odor V.A. Section IV - Fire and Ex Flash Point(Method Used) N.I	plosion Haza	r d Data Flamm	N. N. able Limits N.D.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)	N.L
Section III - Physical/Che Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water N.D. Appearance and Odor N.A. Section IV - Fire and Exertian Point(Method Used) N.I Extinguishing Media Use car	plosion Haza	r d Data Flamm	N. N. able Limits N.D.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)	N.D
Section III - Physical/Che Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water N.D. Appearance and Odor V.A. Section IV - Fire and Exection IV - Fire and Exection IV - Ivan Appearance Appearance Appearance Exection IV - Ivan Appearance Execution IV - Ivan Appearance Exection IV - Ivan Appearance Execution IV - Ivan	plosion Haza	r d Data Flamm	N. N. able Limits N.D.	D.		Specific Gravity (H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)	N.L

Permanent Marker Refill Page 2 of 3

Unusual Fire and Explosion	Hazards <i>None</i>					
1						
Section V- Reactivity I	Data					
Stability	Unstable		Conditions to Avoid			
	Stable	X	None			
Incompatibility (Materials to Avoid)	None					
Hazardous Decomposition or Byproducts	None					
Hazardous Polymerization	May Occur		Condition to Avoid			
	May Not Occur	X	None			
Section VI - Health Ha	zard Data					
Route(s) of Entry:	Inhalation? <i>Yes</i>	Skin? Yes	Ingestion? Yes			
Health Hazards(Acute and C	hronic) N.D.					
Carcinogenicity:	NTP? None	IARC Monographs?	OSHA Regulated? <i>None</i>			
		None				
Signs and Symptoms of Exp	osure <i>N.D</i> .					
Medical Conditions						
Generally Aggravated by Ex	posure <i>N.D</i> .					
		ve to fresh air; seek medical. In				
		nedical. Skin: Wash off in flowi	ng water; seek medical			
Section VII - Precaution	<u> </u>					
Steps to Be Taken in Case M						
Soak up with absorbent	t materials. (Paper/Clo	oth)				
Waste Disposal						
In accordance with nat		regulations.				
Precautions to Be Taken in F						
Avoid high temperature	2.					
Other Precautions <i>N.A.</i>						
Section VIII - Control	Measures					
Respiratory Protection(Speci	ify Type) N.A.					
Ventilation	Local Exhaust N.A. Special N.A.					
	Mechanical(G		r N.A.			

Protective Gloves	Eye Protection
<i>N.A.</i>	<i>N.A.</i>
Other Protective Clothing or Equipment	
<i>N.A.</i>	
Work/Hygienic Practices	
N.A.	

