



January 2015

1. Identification

Name of the product: ReadRight KeyboardKleen Kit

Product Identification Number(s): RR1263

Recommended use: Surface wipe Use not recommended: Body wipe

Company: Advantus Corporation Telephone: 904-482-0091

 12276 San Jose Blvd., Ste. 618
 Fax number:
 904-482-0099

 Jacksonville, FL 32223
 Emergency:
 1-800-327-1237

CHEMTREC (Transportation): 1-800-424-9300

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA). It is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulation.

2. Hazard(s) identification

Emergency Overview

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

Other hazards which do not result in classification are: May form explosive peroxides.

GHS Classification

Flammable liquids (Cat. 2) H225 Highly flammable liquid and vapor.

Skin irritation (Cat. 3) H316 Causes mild skin irritation. Eye irritation (Cat. 2A) H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure (Cat. 3) GHS Label elements, including precautionary statements

Pictogram:



Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ s/ spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3. Composition / Information on ingredients

Chemical identity: 2-Propanol (solution) 91%
Common name: Isopropyl alcohol, Rubbing alcohol

Numbers of identity: CAS. 67-63-0 EINECS. 200-661-7

Chemical identity: Water 9%

Common name: Water

Numbers of identity: CAS 7732-18-5 EINECS 231-791-2

Impurities: None of toxicological significance.

4. First-aid measures

P304+313 +341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing. Consult a physician.

P302+352 IF ON SKIN: Wash with soap and water.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.

Remove contact lenses if present and easy to do; continue rinsing.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed: Severe eye irritation. Skin irritation.

5. Firefighting measures

Suitable extinguishing equipment:

Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Emergency procedures:

Eliminate ignition source. Evacuate unnecessary personnel. Call appropriate fire fighting crew.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous decomposition products formed under fire conditions. - Carbon oxides, product vapors.

Use water spray to cool unopened containers.

6. Accidental release measures

Use personal protective equipment. Avoid breathing, mist or vapors. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Be aware of possible accumulating vapors which could form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then absorb with industrial absorbent, or collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

See also Sec. 13.

7. Handling and storage

Precautions for safe handling:

Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking.

Prevent the build up of electrostatic charge.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place.

Containers which have been opened must be resealed and kept upright to prevent leakage.

8. Exposure controls / personal protection

Information on the system design:

Product is intended for external use only. Stay up wind, out of any spray developed.

Exposure Limits: Reference 29CFR 1910.1000 Table Z-1 Component Name, CAS# OSHA PEL OSHA STEL

2-Propanol 67-63-0 400 ppm 980 mg/m3 500 ppm 1,225 mg/m3

Personal protective equipment :

Respiratory protection: Where appropriate use a full-face supplied air respirator.

Hand protection: Rubber gloves.

Eye protection: Safety glasses with side-shields.

Skin and body protection: Chemical resistant apron or protective suit if splashing or repeated contact

with solution is likely; flame retardant and antistatic properties are recommended.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Wash hands and face before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance: Clear, colorless liquid

Odor: Alcoholic

Odor threshold: The highest known value is 22 ppm (Isopropyl alcohol)

pH-value: Approx. 7-9
Melting point: no data available
Freezing Point: no data available
Initial boiling point: no data available

Flash point: 18 °C (65 °F) - closed cup (approximate)

Evaporation rate: no data available Flammability (solid, gas): Not applicable

Explosion limits: Lower: 2% Upper: 12.7% (Isopropyl alcohol) Vapor pressure: (highest partial vapor pressure) at 20°C: Not available

Vapor density: Not available

Relative density (water=1.00): 0.80 g/cm3 approx. Auto-ignition temperature: Not available Solubility: Totally soluble in water at 20°C Decomposition temperature: Not available

Partition coefficient: Log Kow = Not applicable to mixture. Viscosity: Like water

10. Stability and reactivity

Chemical stability: No decomposition, if used according to specifications. Possibility of hazardous reactions: May form explosive mixture with air.

Conditions to avoid: Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid: Aluminum, Acids, Oxidizing agents, Halogenated compounds, Acid anhydrides

Hazardous decomposition products: Carbon oxides, product vapors.

11. Toxicological information

There is no data available for the product.

Routes of Entry: Absorbed through skin. Eye contact. Inhalation.

2-Propanol

Oral Toxicity LD 50: 5143 mg/kg (Mouse) (Calculated value for 70% in water mixture)
Dermal Toxicity LD 50: 18286 mg/kg (Rabbit) (Calculated value for 70% in water mixture)

Inhalation Toxicity, Vapor, LC50 No data. Eye Irritation (Rabbit) No data. Dermal Irritation (Rabbit) No data.

Chronic Effects on Humans:

No component listed by NTP, IARC, OSHA or ACGIH as a suspect or potential carcinogen. California Prop. 65 chemicals: This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other reproductive harm.

Contains material which may cause damage to the following organs: kidneys, liver, CNS,

Signs and Symptoms of Exposure:

Central nervous system depression, prolonged or repeated exposure can cause:, nausea, dizziness, narcosis, drowsiness,

12. Ecological information

Ecotoxicity: Not available for the product. BOD and COD: Not available.

Products of Biodegradation:

Hazardous short term degradation products are not likely, but long term degradation products may arise. Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

PBT and vPvB assessment:

Persistence and degradability:

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

No data available.

13. Disposal considerations

Burn in a chemical incinerator equipped with an afterburner and scrubber.

Dispose in accordance with local, state and federal regulations.

14. Transport information

DOT (US)

UN number: 3175 Class 4.1 Label: 4.1 Packing group: II

Proper shipping name: Solids containing flammable liquid, n.o.s. (Isopropanol)

Reportable Quantity (RQ): Not applicable

Marine pollutant: No May also be shipped Consumer Commodity ORM-D

The description shown may not apply to all shipping situations. Consult 49CFR, OSHA or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name, labeling)

and mode-specific or quantity-specific shipping requirements,

15. Regulatory information

OSHA Hazards: Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

SARA 302 Components: Non

SARA 313 Components: Isopropanol CAS 67-63-0

Inventory Status: All components are on TSCA, EINECS/ELINCS, AICS, and DSL.

Federal and State Regulations:

State Right to Know lists (RTK): 2-Propanol: FL, IL, MA, MN, NJ, PA, RI,

Water: Ma. PA. NJ

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B:

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B:

Material causing other toxic effects: None

California Prop. 65 Components: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. Other information

SDS Preparation date:	Janua	ary 5, 2015			
Hazard Categories:	Health	Fire	Pressure	Reactivity	Reference 49 CFR 171.8,
Immediate	Yes	Yes	No	No	OSHA 29 CFR 1910.1200 and
Delayed	Yes	No	XXX	XXX	SARA 302/311/312/313.
HMIS Hazard ratings: Health 2 Fire 3 Instability 0 Other B (Goggles, gloves)					
Hazard Ratings: Least: 0 Slight: 1 Moderate: 2 High: 3 Extreme: 4					

HMIS® is a registered trade and service mark of the NPCA.

Note: The information in this SDS was obtained from current reputable and competent sources. However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for the use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.

This MSDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA).