

# Office Products Group

## **MATERIAL SAFETY DATA SHEET**

MSDS # 63701

Section One: Identification

Sanford, L.P. 2707 Butterfield Road Oak Brook, IL 60523 USA 800-323-0749 or 630-481-2000 **EMERGENCY MEDICAL NUMBER:** 

888-786-0972

Product Name: Uni-Paint Px-21 Fine and Px-20 Medium Marker

Colors: White, Yellow, Orange, Green, Lt Blue, Blue, Violet, Pink, Red, Black, Gold, Silver

Writing Instrument Manufacturers Association (WIMA) certified. Conforms to ASTM D-4236. These markers and the inks contained within have been examined by the WIMA Board Certified Toxicologist in a program of toxicological evaluation to assure they are in compliance with Federal Hazardous Substances Act (FHSA), Labeling of Hazardous Art Materials Act (LHAMA), and ASTM D-4236.

#### Section Two: Hazard Identification

Acute hazard: At high concentration, dizziness, drowsiness, and unconsciousness may occur. CAUTION: Contains xylene. Harmful or fatal if swallowed. KEEP OUT OF REACH OF CHILDREN. Direct contact may cause skin or eye irritation.

\*\*WARNING: This product contains a chemical known to the State of California to cause cancer.

#### Section Three: Composition

Xylene (1330-20-7), pigments, resin, dyes

#### Section Four: First Aid Measures

Inhalation: Move person to fresh air if symptoms persist, seek medical attention.

Skin Contact: Wash with soap and water.

Eye Contact: Flush with water. If irritation persists, seek medical attention.

Ingestion: Contact physician immediately! DO NOT induce vomiting. Do Not give anything by mouth.

# Section Five: Fire Fighting Measures

Flash Point: 27-32C<sub>xylene</sub> (CC)

Flammability Limits (% by volume): Lower: 1.1% Upper: 6.4%

Extinguishing Media: Dry chemical, carbon dioxide, regular foam

Special Fire Fighting Measures: For large fires, use foam or flood with fine water spray.

Unusual Fire and Explosion Hazards: Avoid inhalation of material or combustion by-products. Stay upwind.

#### Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Treat as flammable solvent. Use adequate ventilation.

## Section Seven: Handling and Storage

Handling: Keep marker capped when not in use. Avoid unnecessary contact with skin. Use in well ventilated area.

Storage: Keep away from Heat and open flame. KEEP OUT OF REACH OF CHILDREN.

# Section Eight: Exposure Controls and Personal Protection

Eye Protection: None under normal use conditions.

Clothing: None under normal use conditions.

Respirator: None under normal use conditions.

Ventilation: Use in a well ventilated area.

February 10, 2011 Page 1 of 2



# Office Products Group

## **MATERIAL SAFETY DATA SHEET**

MSDS # 63701

Section Nine: Physical and Chemical Properties

For ink unless otherwise specified:

Boiling Point: 138.5C (xylene) Specific Gravity: 1.25 - 1.32

Vapor Pressure: 6.72 mm Hg at 21C

Solubility in Water: Insoluble

Evaporation Rate: Not available

Appearance/Odor: Colored ink; xylene odor

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Avoid heat, flames, sparks, and other sources of ignition.

Chemical Incompatibility: Strong oxidizers

Hazardous Decomposition: Oxides of carbon in fire situation.

Hazardous Polymerization: Will not occur.

Section Eleven: Toxicological Information

See Section Two: Hazard Identification for any hazards

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

DOT: ORM-D Consumer Commodity

IATA: Consumer Commodity, 9, ID8000, packing instruction Y963

IMO: Not determined

Section Fifteen: Regulatory Information

TSCA: The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory.

All ingredients used to manufacture this product are listed on the TSCA Inventory

\*\*WARNING: This product contains a chemical known to the State of California to cause cancer\*\*

Health
Flammability
Reactivity
Personal Protection

HMIS Code

2
NewellRubbermation
Standard and the product describe CFR 1910.12000
Hazardous Prod
MSDS is forward

NewellRubbermaid, Inc (Sanford L.P) has been advised by Counsel that the OSHA Hazard Communication Standard and the Health Canada Workplace Hazardous Materials Information Standard do not apply to the product described in this Material Safety Data Sheet. The reasons for the exemptions are contained in 29 CFR 1910.1200(b)(6)(ix) as amended Sept 14, 2009 per the Code of Federal Regulations and also Canadian Hazardous Products Act part 12 section (f) as amended June 1, 2009. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by nor is this MSDS meant to comply with all requirements of the hazard communication standards.

0=Minimal / 4 = Severe

February 10, 2011 Page 2 of 2