

# **SERIES 42**

## **Premium Narrow Channel**



Premium grade narrow channel fixture. For use in indoor applications such as factories, warehouses, workshops, garages utility areas, coves and public buildings where industrial grade is required.

- · Snap-on components for easy assembly and maintenance
- Versatile end plate doubles as coupler for continuous row mounting
- · Asymmetric and symmetric reflectors sold separately
- Narrow body width 2 3/4" nominal
- · Surface, stem or chain mountable
- · UL listed for damp location

#### CONSTRUCTION

Housing is die-formed from cold rolled steel. Finish is high reflectance baked white enamel. Single wireway cover on non-tandem units. Knockouts are provided for stem mounting. Mounting holes are provided.

## SIZE W x L x H in inches (mm)

2.75W x 1.80H

Fixture length = lamp(s) length



#### **EZ LED**

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. EZ LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, EZ LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

### **Lamp Specifications:**

Our T8 LED lamps are available in 2, 3 and 4 ft. sizes in different wattage, lumens and color temperature options. See lamp options and specs at www.mobern.com/EZLEDLamps.


50,000 Hour Life with 5 Year Warranty Aluminum Base and Aluminum Housing Operating Temperature: - 20°C to 50°C

Color Temperature: 3000K, 3500K, 4000K, 5000K G13 Pins (Same as Fluorescent Linear T8 Bipin)

AC100 - 277V

#### **Emergency Options:**

The standard EZ LED Lamps require an inverter or an All-inone emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.mobern.com/ EZLEDemergency.



Mobern reserves the right to substitute our own UL DLC listed tubes.

Mobern Lighting

8200 Stayton Dr. Suite 500 Jessup, MD 20794 Phone: 800.444.9288 Fax: 972-247-0200 www.mobern.com email: sales@mobern.com

Catalog Number:

Notes: