

Version 3.0

Revision Date 08/31/2015

Print Date 10/14/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A07872 ZEP PRO HI PERF ADH R34901 20n14
Material number	:	0000000001046691
Manufacturer or supplier's details		
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers	
For SDS Information	: Compliance Services 1-877-428-9937
For a Medical Emergency	: 877-541-2016 Toll Free - All Calls Recorded
For a Transportation	: CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency	In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless, light yellow
Odour	solvent-like

GHS Classification

Flammable aerosols Gases under pressure Skin irritation Eye irritation Specific target organ toxicity - single exposure	 Category 1 Liquefied gas Category 2 Category 2A Category 3 (Central nervous system)
GHS Label element	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	: Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.



sion 3.0	Revision Date 08/31/2015 Print Date 10/14/2015
	 P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear eye protection/ face protection. P280 Wear protective gloves. Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and wate P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.
Potential Health Effects	
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 10 - < 20



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0

Revision Date 08/31/2015

Print Date 10/14/2015

propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20
cyclohexane	110-82-7	>= 10 - < 20
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 5 - < 10
Aromatic Hydrocarbon Resin	68410-16-2	>= 5 - < 10
methyl acetate	79-20-9	>= 5 - < 10

SECTION 4. FIRST AID MEASURES

General advice	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
In case of skin contact	 If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes.
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water for at least 15 minutes.
If swallowed	 Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This



Version 3.0	Revision Date 08/31/2015	Print Date 10/14/2015
	must not be discharged into drai Fire residues and contaminated be disposed of in accordance wi For safety reasons in case of fire separately in closed containmen Use a water spray to cool fully c	fire extinguishing water must th local regulations. e, cans should be stored its.
Special protective equipn for firefighters	nent : Wear self-contained breathing a necessary.	pparatus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling :	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Do not breathe vapours or spray mist. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use.
Conditions for safe storage :	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep in a dry, cool and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid :	Strong oxidizing agents



Version 3.0

Revision Date 08/31/2015

Print Date 10/14/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
cyclohexane	110-82-7	TWA	100 ppm	ACGIH
		TWA	300 ppm 1,050 mg/m3	NIOSH REL
		TWA	300 ppm 1,050 mg/m3	OSHA Z-1
		TWA	300 ppm 1,050 mg/m3	OSHA P0
methyl acetate	79-20-9	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 610 mg/m3	NIOSH REL
		ST	250 ppm 760 mg/m3	NIOSH REL
		TWA	200 ppm 610 mg/m3	OSHA Z-1
		TWA	200 ppm 610 mg/m3	OSHA P0
		STEL	250 ppm 760 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	50 mg/l	ACGIH BEI
				shift (As	-	



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0

Print Date 10/14/2015

	soon as	
	possible	
	after	
	exposure	
	ceases)	

Revision Date 08/31/2015

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: A	erosol containing a liquefied gas
Colour	: C	olourless, light yellow
Odour	: S	olvent-like
Odour Threshold	: N	lo data available
рН	: N	lot applicable
Melting point/freezing point	: N	lo data available
Boiling point	: N	lo data available
Flash point	: N	lo data available
Evaporation rate	: >	1
Flammability (solid, gas)	: E	extremely flammable aerosol.
Upper explosion limit	: N	lo data available
Lower explosion limit	: N	lo data available
Vapour pressure	: N	lo data available
Relative vapour density	: N	lo data available



Version 3.0	Revision Date 08/31/2015	Print Date 10/14/2015
Density	: 0.86 g/cm3	
Solubility(ies)		
Water solubility	: soluble in cold water, soluble in he	ot water
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

acetone:	
Acute oral toxicity	: LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h
	LC50 Rat: 50.1 mg/l
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg
	LD50 Rabbit: > 7,426 mg/kg

propane:



A07872 ZEP PRO HI PERF ADH R34901 20n14

		Print Date 10/14/201
Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 658 mg/l Exposure time: 4 h	
	LC50 Rat: 1,355 mg/l	
butane:	LC50 Mouse: 1,237 mg/l	
Acute inhalation toxicity	Exposure time: 2 h	
	LC50 Rat: 1,355 mg/l	
cyclohexane:		
Acute oral toxicity	: LD50 Oral Rat: 12,705 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 13,900 mg/l Exposure time: 4 h	
Acute dermal toxicity	: LD50 Dermal Rabbit: > 2,000 mg/kg	
kin corrosion/irritation		
Product:		
Remarks: May irritate skin.		
Serious eye damage/eye irritation		
Product:		
Remarks: Irritating to eyes.		
Respiratory or skin sensitisation		
lo data available		
Germ cell mutagenicity		
lo data available		
Carcinogenicity		
lo data available		
Reproductive toxicity		
No data available		
acetone: propane: butane:		
cyclohexane: Naphtha (petroleum), hydrotr Aromatic Hydrocarbon Resin methyl acetate:		



Version 3.0

Revision Date 08/31/2015

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioacci imulativ -o noter

Bioaccumulative potentia	ıl
--------------------------	----

<u>i i oddoti.</u>	
Partition coefficient: n- octanol/water <u>Components:</u> butane :	Remarks: No data available
octanol/water	: Pow: 2.89
cyclohexane :	
Partition coefficient: n-	: log Pow: 3.44
Mobility in soil	
No data available	
Other adverse effects	
No data available <u>Product:</u>	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).



Version 3.0	Revision Date 08/31/2015	Print Date 10/14/2015
Additional ecological information	: An environmental hazard canne event of unprofessional handlir	

aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
cyclohexane	110-82-7	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity



A07872 ZEP PRO HI PERF ADH R34901 20n14

Version 3.0	Revision Date 08/31/2015	Print Date 10/14/2015
This material does not co	ontain any components with a section 304 El	HS RQ.

SARA 311/312	Hazards :	Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard		
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.		
SARA 313	:	: The following components are subject to reporting levels		evels
		established by SARA Title III, Sect cyclohexane	110-82-7	10.0749 %
California Prop 65		WARNING! This product contains a chemical known to the State of California to cause cancer.		
	naphthalene		91-20-3	
	benzene	WARNING: This product contains	71-43-2	a ta tha
		WARNING: This product contains State of California to cause birth d harm.		
	benzene		71-43-2	
	toluene		108-88-3	

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	This product contains one or several components that are not on the
	Canadian DSL nor NDSL.
AICS	Not in compliance with the inventory
NZIOC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION




Version 3.0

Revision Date 08/31/2015

Print Date 10/14/2015

Further information



OSHA GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	 Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.0
Revision Date:	08/31/2015
Print Date:	10/14/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next



Version 3.0

Revision Date 08/31/2015

Print Date 10/14/2015

Dimension[™], Petro[®], i-Chem[®], TimeMist[®], TimeWick[™], MicrobeMax[®], Country Vet[®], Konk[®], Original Bike Spirits[®], Blue Coral[®], Black Magic[®], Rain-X[®], Niagara National[™], FC Forward Chemicals[®], Rexodan[®], Mykal[™], and a number of private labeled brands.