



Catalog Number 39010  
 UPC Number 60198639010  
 Description Fixed Base Shutter Style Photocell  
 120 Volt



**Features**

- Housing: UV stabilized impact resistant Polycarbonate  
 Heavy-duty thermal bi-metal switch provides a 30+ second time delay  
 Contact Position at Night is Normally Closed
- Sensor Type: CDS  
 Single Pole, Single Throw Switch  
 Power Consumption Below 1.5 Watts Average
- Load Switching Capability: 5,000 operations
- Load Rated: 600W/1000W/1800VA  
 3/4" Long 3/8" Threaded Nipple & Nut for 1/2" K.O.
- Operating Temperature: -40°C to +70°C

**General**

Material: Polycarbonate Housing  
 Switching: Single Pole Single Throw, Normally Closed  
 Load Rating: 2000W Tungsten  
 1000VA HID  
 Sensor Type: CDS

**Dimension Information**

Width: 2.05"  
 Height: 3.6"  
 Depth: 1.4"  
 Lead: 16AWG/18AWG, LENGTH 15" 105°C  
 Nipple: 1/2"-14 Thread for 1/2" KO

**Specifications**

Photocell: Cadmium Sulfide  
 Temperature Rating: Neg 40F To +140°F  
 Voltage Rating: 120 V  
 Frequency: 50-60 Hertz  
 Turn-On Light Level: 1-5 FC  
 Turn-Off Light Level: 3-5 FC  
 Turn-On Time Delay: 30 Seconds Minimum  
 Turn-Off Time Delay: 30 Seconds Minimum

**Packaging**

Bag Qty 1  
 Master Bag Qty 1

**Certifications**

UL UL 773 Standard  
 cUL  
 RoHS

